



ACABADOS



- KRION CEMENT NATURE. REF26023. LIJA 240
 KRION CLAY NATURE. REF 26020. LIJA 240
 ACERO INOX SATINADO ESTANDAR REF2202
 LOGO REHUNDIDO 3mm



ALZADO







PERFIL



PLANTA

PLANTA BASE


QTY数量	DESCRIBE描述	SUPPLIER供应部门	REFERENCE参考信息	MATERIAL材料	FINISH颜色	PROCESSES工艺	UNIT WEIGHT单件重量(Kg)	TOTAL WEIGHT总重量(Kg)
	8Z125PMR	SUPPLIER	REFERENCE	防火MDF/Stainless/KRION	双贴黑三胺/拉丝/PENDING	cut/weld/drill/polish/paint	145.45	



- 技术要求(Technical Requirements):
- 1、供货方要相应配同色的连接件; 螺柱类连接件要装在相应位置, 以防止孔位偏差;
(The supplier needs to provide the connector and match the color;
The threaded rod must be pre-install into the correct location to avoid the deviation)
 - 2、金属件要求无破锋, 焊接牢固, 无虚焊, 承重部位必须满焊;
(The metal parts must be smoothly, strong welding, full weld on the loading location)
 - 3、金属件所有见光部位不允许有影响外观效果的焊疤;
(Forbid the welding mark on the appearance surface of metal parts)
 - 4、注意公差配合: 镜子和玻璃尺寸, 需与挂臂配合的挂钩内卡口, 如未注明公差按负公差0.5mm加工.
(Take note the tolerance for mirror, glass, the hook which needs to assembled with bar and so on, the unspecified tolerance is -0.5mm.)
 - 5、所有可见螺丝均为内六角螺丝;
(All the appearance screws must be allen screws)
 - 6、所有镜子、玻璃、大理石4边和4角都要磨边, 金属件所有边角无破锋\无毛刺, 防止伤人.
(All mirrors, glass, marble 4 sides and 4 angles need to sanding, all corners of metal furniture need to polish, no burr, prevent injuries.)
 - 7、凡是涉及到走线的产品, 供货方必须穿好电线.
(The supplier must wear all wire.)
 - 8、供货方必须装配好由供货方生产的配套产品, 例如层板托、连接件.
(the supplier must Pre assembled accessory, such as lamination, connector.)
 - 9、所有部件焊接时要磨45°左右的斜边, 辅助焊接, 超过轮廓线外的焊点要磨平。

SHEET FORMAT 图纸大小		A3	UNITS单位	mm	8Z125PMR	-总图	PROJECT NO.内部单号		STORE CODE店辅号	
DRAWN BY制图		DevinDong	SCALE比例	1:15			0000/00		0000	
ORDER DATE下单日期		00/00/00	DELIVERY DATE入库日期	00/00/00			ORDER NO.订单号			
CLIENT DRAWING图户图		Proy V.0	VERSION版本	V.0			000			
ASSEMBLED IN:组装场所		DRAWING TYPE图纸类型		MANUFACTURING	----	----	ZARA			
INTERIOR					----	----				

QTY数量	DESCRIBE描述	ZARA CODE	REFERENCE参考信息	MATERIAL材料	FINISH颜色	PROCESSES工艺	UNIT WEIGHT单件重量(Kg)	TOTAL WEIGHT总重量(Kg)
	8Z125PMR		REFERENCE	防火MDF/Stainless/KRION	双贴黑三胺/拉丝/PENDING	cut/weld/drill/polish/paint	145.45	



No. 序号	Part Description零件描述	Quantity数量	Material材质	Finish颜色
1	5Z125PMR-0202	1	MDF	双贴黑三胺
2	5Z125PMR-0501	1	KRION	PENDING
3	5Z125PMR-0503	1	KRION	PENDING
4	5Z125PMR-0104	1	Stainless 不锈钢	拉丝
5	5Z140 PERCHAS BOLSAS L 0105	1	Stainless不锈钢	拉丝
6	5Z140 PERCHAS BOLSAS L 0107	1	Stainless不锈钢	拉丝
7	5Z140 PERCHAS BOLSAS L 0106	1	Stainless不锈钢	拉丝
8	5Z125LEFT-0102	1	Stainless不锈钢	拉丝
9	5Z140 PERCHAS BOLSAS L 0112	1	Stainless不锈钢	拉丝
10	5ZPMR R-0106	1	Stainless 不锈钢	拉丝

技术要求(Technical Requirements):

1、供货方要相应配同色的连接件;螺栓类连接件要装在相应位置,以防止孔位偏差;
(The supplier needs to provide the connector and match the color;
The threaded rod must be pre-install into the correct location to avoid the deviation)

2、金属件要求无披锋,焊接牢固,无虚焊,承重部位必须满焊;
(The metal parts must be smoothly, strong welding, full weld on the loading location)

3、金属件所有见光部位不允许有影响外观质量的焊疤;
(Forbid the welding mark on the appearance surface of metal parts)

4、注意公差配合:镜子和玻璃尺寸,需与挂臂配合的挂钩内卡口,如未注明公差按负公差0.5mm加工.
(Take note the tolerance for mirror, glass, the hook which needs to assembled with bar and so on, the unspecified tolerance is -0.5mm.)

5、所有可见螺丝均为内六角螺丝.
(All the appearance screws must be allen screws)

6、所有镜子、玻璃、大理石4边和4角都要磨边,金属件所有边角无披锋\无毛刺,防止伤人.
(All mirrors, glass, marble 4 sides and 4 angles need to sanding, all corners of metal furniture need to polish, no burr, prevent injuries.)

7、凡是涉及到走线的产品,供货方必须穿好电线.
(The supplier must wear all wire.)

8、供货方必须装配好由供货方生产的配套产品,例如层板托、连接件.
(the supplier must Pre assembled accessory, such as lamination, connector.)

9.所有部件焊接时要露45°左右的斜边,辅助焊接,超过轮廓线外的焊点要磨平。

SHEET FORMAT 图纸大小	A3	UNITS单位	mm	8Z125PMR	-爆炸图	PROJECT NO.内部单号	STORE CODE店铺号
DRAWN BY制图	DevinDong	SCALE比例	1:15			0000/00	0000
ORDER DATE下单日期	00/00/00	DELIVERY DATE入库日期	00/00/00			ORDER NO.订单号	000
CLIENT DRAWING图产图	Proy V.0	VERSION版本	V.0			ZARA	
ASSEMBLED IN-组装场所	INTERIOR	DRAWING TYPE图纸类型	MANUFACTURING			CAAMAÑOASIA®	