







ACABADOS

- 1 METAL LACADO NEGRO PINTURA POLVO 0102. REF:2505
- 2 ACABADO PARED
- 3 TARIMA UNDORA TRAVERTINO NAVONA GRIS EXTRA MATE REF:2507 SENTIDO LONGITUDINAL
- 4 ACERO INOX SATINADO ESTANDAR. REF 2202



DOTACION

DESCRIPCION	Uds
FRONTAL EXTRAIBLE (TUBO MACIZO)	6

QTY数量	DESCRIBE描述	SUPPLIER供应部门	REFERENCE参考信息	MATERIAL材料	FINISH颜色	PROCESSES工艺	UNIT WEIGHT单件重量 (Kg)	TOTAL WEIGHT总重量 (Kg)
	8Z70468900	SUPPLIER	REFERENCE	IRON铁/Stainless不锈钢/防火MDF	2505/2507/2202/防锈底漆		67.52	

No. 序号	Part Description零件描述	Quantity数量	Material材质	Finish颜色
1	5Z72468903	1	防火MDF	TARIMA UNDORA TRAVERTINO NAVONA GRIS EXTRA MATE REF:2507 SENTIDO LONGITUDINAL
2	5Z71468905	1	IRON铁	防锈底漆
3	5Z71468904	2	IRON铁	防锈底漆
4	5Z72468902	2	防火MDF	TARIMA UNDORA TRAVERTINO NAVONA GRIS EXTRA MATE REF:2507 SENTIDO LONGITUDINAL
5	5Z71468901	1	Stainless不锈钢	METAL LACADO NEGRO PINTURA POLVO 0102. REF:2505/压条_2202
6	5Z71472903	5	IRON铁	防锈底漆
7	5Z71472905	1	IRON铁	防锈底漆
8	5Z71205403	6	304#	METAL LACADO NEGRO PINTURA POLVO 0102. REF:2505/压条_2202号不锈钢细拉丝

技术要求(Technical Requirements):

1、供货方要相应配同色的连接件; 螺杆类连接件要装在相应位置, 以防止孔位偏差;
(The supplier needs to provide the connector and match the color; The threaded rod must be pre-install into the correct location to avoid the deviation)

2、金属件要求无披锋, 焊接牢固, 无虚焊, 承重部位必须满焊;
(The metal parts must be smoothly, strong welding, full weld on the loading location)

3、金属件所有见光部位不允许有影响外观效果的焊疤;
(Forbid the welding mark on the appearance surface of metal parts)

4、注意公差配合: 镜子和玻璃尺寸, 需与挂臂配合的挂钩内卡口, 如未注明公差按公差0.5mm加工.
(Take note the tolerance for mirror, glass, the hook which needs to assembled with bar and so on, the unspecified tolerance is -0.5mm.)

5、所有可见螺丝均为内六角螺丝.
(All the appearance screws must be allen screws)

6、所有镜子、玻璃、大理石4边和4角都要磨边, 金属件所有边角无披锋\无毛刺, 防止伤人.
(All mirrors, glass, marble 4 sides and 4 angles need to sanding, all corners of metal furniture need to polish, no burr, prevent injuries.)

7、凡是涉及到走线的产品, 供货方必须穿好电线.
(The supplier must wear all wire.)

8、供货方必须装配好由供货方生产的配套产品, 例如层板托、连接件.
(the supplier must Pre assembled accessory, such as lamination, connector.)

9. 所有部件焊接时要磨45°左右的斜边, 辅助焊接, 超过轮廓线外的焊点要磨平.

SHEET FORMAT 图纸大小	UNITS单位	8Z70468900	-bom	PROJECT NO.内部单号	STORE CODE店铺号
A3	mm			0000/00	0000
DRAWN BY制图	SCALE比例			ORDER NO.订单号	000
JerryLu	1:25			ZARA	
ORDER DATE下单日期	DELIVERY DATE入库日期				
00/00/00	00/00/00			CAAMAÑOASIA®	
CLIENT DRAWING图户图	VERSION版本				
Proy V.0	V.0				
ASSEMBLED IN: 组装场所	DRAWING TYPE 图纸类型				
INTERIOR	MANUFACTURING				

